



Product Description:

Product Image:



Line Drawing



Product Specs:

Technology	LED	Input Voltage	220-240V AC	
Positional Adjustment	Fixe	Number of LEDs	20	
Lifetime L70 (hrs)	35000	Input Frequency	50/50HZ	
Dimmable	Oui	Dali	Non	
IP Rating	IP65	Fire Protection	Oui	
Acoustic Rated	Oui	Operating Env. Temp. (Min) °C	-20°C	
Operating Env. Temp. (Max) °C	25°C	Optic Material	Verre	
Power Factor	0.9	Overall Diameter (mm)	88	
Height (mm)	80	Recess Depth (mm)	80	
Cutout Diameter (mm)	70	Weight (Kg)	0.236	

SKU Table and Ordering:

SKU Code	Wattage	ColorTemp	Lumens	BeamAngle	SKUType	FinishColor
AU-CX7	7	3000K	580	60	Dimmable	White
AU-CX7	7	4000K	620	60	Dimmable	White
AU-CX7	7	5700K	620	60	Dimmable	White

Compliance & Approvals:











AU-CX7 Last revised 02nd November 2021 http://auroralighting.com

Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW United Kingdom

Tel: +44 (0) 1707 228 700

AU-CX7 Last revised 02nd November 2021 http://auroralighting.com