


Product Description:

Le tubulaire LED étanche IP69K LinearTube™ est conçue pour fonctionner dans des environnements où un éclairage robuste est requis, par exemple l'industrie alimentaire ou les sites agricoles. Le tubulaire LED peut résister à un lavage à grande eau et à une température ambiante de fonctionnement de -20° à 45°. Elle peut être montée en surface ou suspendue, pour une efficacité de 120 lm/W. Le dissipateur thermique interne en aluminium offre une meilleure dissipation de la chaleur, et le diffuseur entièrement en polycarbonate est classé IK10 pour sa résistance aux chocs.


Product Image:



Line Drawing



Polar Curve



Product Specs:

Technology	LED	Input Voltage	200-240V AC
Number of LEDs	442	Lifetime L70 (hrs)	50000
Dimmable	Non	IP Rating	IP69K
IK Rating	IK10	Operating Env. Temp. (Min) °C	-20°C
Operating Env. Temp. (Max) °C	45°C	Power Factor	0.9
Overall Diameter (mm)	70	Length (mm)	1500
Weight (Kg)	2.056		

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	CRI	Colour	Finish Colour
EN-ANTB1500FB/40	50	140	7200	144	80	4000	Blanc Dépoli

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office

Apex Park

6 Little Burrow

Welwyn Garden City AL7 4SW

United Kingdom

Tel : +44 (0) 1707 228 700